

CUSTOMER NO.: 24498
Serial No. 10/789,425
Reply to Office Action dated: 7/30/07
Response dated: 11/20/07

RECEIVED
CENTRAL FAX CENTER

PATENT
PRN-012

DEC 14 2007

Amendments to the Claims

Please amend claims 1, 3, 5, 7, 8, 10, 12, 14, 16, 18, 21, 22, 24, 25 and 28 as follows:

1. (Currently Amended) A speaker system providing enhanced intelligibility of a reproduced audio program signal in the presence of ambient noise, comprising:
 - means for receiving the reproduced audio program signal;
 - a microphone for monitoring at least ambient noise signals and for providing a microphone output signal;
 - means for enabling the microphone output signal during first increments of time when the reproduced audio program signal is substantially off, and disabling the microphone output signal during second increments of time when the reproduced audio program signal is on, such that the microphone output signal includes ambient noise signal components without including reproduced audio program signal components; and
 - a signal process processor, coupled to in communication with the means for receiving and the means for enabling/disabling, ~~including a first transfer function having a signal process output signal, the for~~ applying a first transfer function to the reproduced audio program signal, the first transfer function providing incrementally increasing gain adjustments to the reproduced audio program signal as a function of an increasing amplitude of the microphone output signal, and ~~vice versa incrementally decreasing gain adjustments to the reproduced audio program signal as a function of a decreasing amplitude of the microphone output signal, wherein the signal process output signal is maintained during such times as the microphone output signal is disabled.~~
2. (Original) The speaker system according to claim 1, wherein the incremental gain adjustments are in steps of between 1 dB and about 10 dB.

CUSTOMER NO.: 24498**Serial No. 10/789,425**

Reply to Office Action dated: 7/30/07

Response dated: 11/20/07

**PATENT
PRN-012**

3. (Currently Amended) The speaker system according to claim 1, further comprising a first amplifier having an input and an output, the first amplifier input coupled to the ~~signal-process~~ output signal of the ~~signal process~~ processor and the first amplifier output coupled to an ~~a first speaker~~ input of a first speaker.
4. (Original) The speaker system according to claim 3, wherein the first speaker comprises a single speaker driver having a diaphragm diameter not greater than about 100 centimeters (cm).
5. (Currently Amended) The speaker system according to claim 3, further comprising:
- a low-pass filter having an input and an output, the filter input coupled to the ~~signal-process~~ output signal of the ~~signal process~~ processor and the filter output augmenting the first speaker output in a low frequency region; and
 - a second amplifier having an input and output, the ~~first~~ second amplifier input coupled to the filter output and the ~~first~~ second amplifier output coupled to ~~a second speaker~~ an input of a second speaker.
6. (Original) The speaker system according to claim 5, wherein the first and second speakers each comprise a single speaker driver having a diaphragm diameter not greater than about 100 centimeters (cm).
7. (Currently Amended) A speaker system providing enhanced intelligibility of a reproduced audio program signal in the presence of ambient noise comprising:
- means for receiving the reproduced audio program signal;
 - a microphone for monitoring ambient noise signals and for providing a microphone output signal;
 - means for enabling the microphone output signal during first increments of time when the reproduced audio program signal is substantially off, and disabling the microphone output signal during second increments of time when the reproduced audio program signal is on, such that the microphone output signal includes ambient noise signal

CUSTOMER NO.: 24498**Serial No. 10/789,425**

Reply to Office Action dated: 7/30/07

Response dated: 11/20/07

**PATENT
PRN-012**

includes ambient noise signal components without including reproduced program signal components; and
a signal ~~process~~ processor, ~~coupled to in communication with~~ the means for receiving and the means for enabling/disabling, ~~including a second transfer function having a signal process output signal, the for~~ applying a second transfer function to the reproduced audio program signal, the transfer function ~~providing~~ increasing high frequency response of the reproduced audio program signal as a function of a decreasing amplitude of the microphone output signal, and vice versa, wherein the signal process output signal is maintained during such times as the microphone output signal is disabled.

8. (Currently Amended) The speaker system according to claim 7, further comprising a first amplifier having an input and an output, the first amplifier input coupled to the ~~signal process~~ output signal of the signal process processor and the first amplifier output coupled to ~~an a first speaker~~ input of a first speaker.

9. (Original) The speaker system according to claim 8, wherein the first speaker comprises a single speaker driver having a diaphragm diameter not greater than about 100 centimeters (cm)

10. (Currently Amended) The speaker system according to claim 8, further comprising:

a low-pass filter having an input and an output, the filter input coupled to the ~~signal process~~ output signal of the signal process processor and the filter output augmenting the first speaker output in a low frequency region; and

a second amplifier having an input and output, the ~~first~~ second amplifier input coupled to the filter output and the ~~first~~ second amplifier output coupled to a second speaker.

CUSTOMER NO.: 24498**Serial No. 10/789,425**

Reply to Office Action dated: 7/30/07

Response dated: 11/20/07

PATENT**PRN-012**

11. (Original) The speaker system according to claim 10, wherein the first and second speakers each comprise a single speaker driver having a diaphragm diameter not greater than about 100 centimeters (cm).

12. (Currently Amended) A speaker system providing enhanced intelligibility of a reproduced audio program signal in the presence of ambient noise comprising:

means for receiving the reproduced audio program signal;

a microphone for monitoring ambient noise signals and for providing a microphone output signal;

means for enabling the microphone output signal during first increments of time when the reproduced audio program signal is substantially off, and disabling the microphone output signal during second increments of time when the reproduced audio program signal is on, such that the microphone output signal includes ambient noise signal components without including reproduced program signal components; and

a signal ~~process~~ processor, ~~coupled to~~ in communication with the means for receiving and the means for enabling/disabling, including a first transfer function and a second transfer function having at least one signal ~~process~~ processor output signal, wherein:

the first transfer function provides incrementally increasing gain adjustments to the reproduced audio program signal as a function of an increasing amplitude of the microphone output signal, and vice versa;

the second transfer function provides increasing high frequency response of the reproduced audio program signal as a function of a decreasing amplitude of the microphone output signal, and vice versa; and

the at least one signal ~~process~~ processor output signal is maintained during such time as the microphone output signal is disabled.

CUSTOMER NO.: 24498**Serial No. 10/789,425**

Reply to Office Action dated: 7/30/07

Response dated: 11/20/07

**PATENT
PRN-012**

13. (Original) The speaker system according to claim 12, wherein the incremental gain adjustment are in steps of between about 1 dB and about 10 dB.

14. (Currently Amended) The speaker system according to claim 12, further comprising a first amplifier having an input and an output, the first amplifier input coupled to the at least one ~~signal-process~~ output signal of the ~~signal process~~ processor and the first amplifier output coupled to a first speaker.

15. (Original) The speaker system according to claim 14, wherein the first speaker comprises a single speaker driver having a diaphragm diameter not greater than about 100 centimeter (cm).

16. (Currently Amended) The speaker system according to claim 14, further comprising:

a low-pass filter having an input and an output, the filter input coupled to the at least one ~~signal-process~~ output signal of the ~~signal process~~ processor and the filter output augmenting the first speaker output in a low frequency region; and

a second amplifier having an input and output, the ~~first~~ second amplifier input coupled to the filter output and the ~~first~~ second amplifier output coupled to a second speaker input of a second speaker.

17. (Original) The speaker system according to claim 16, wherein the first and second speakers each comprise a single speaker driver having a diaphragm diameter not greater than about 100 centimeters (cm).

18. (Currently Amended) A method of enhanced intelligibility of a reproduced audio program signal in the presence of ambient noise in a speaker system comprising the steps of:

receiving the reproduced audio program signal;

monitoring ambient noise signals using a microphone to provide a microphone output signal;

enabling the microphone output signal during first increments of the time

CUSTOMER NO.: 24498**Serial No. 10/789,425**

Reply to Office Action dated: 7/30/07

Response dated: 11/20/07

**PATENT
PRN-012**

when the reproduced audio program signal is substantially off, and disabling the microphone output signal during second increments of the time when the reproduced audio program signal is on, such that the microphone output signal includes ambient noise signal components without including reproduced program signal components; and

processing the reproduced audio program signal and the microphone output signal using a first transfer function ~~signal~~, the first transfer function having a signal process output signal, the first transfer function providing incrementally increasing gain adjustments to the reproduced audio program signal as a function of an increasing amplitude of the microphone output signal, and ~~vice-versa~~ incrementally decreasing gain adjustments to the reproduced audio program signal as a function of a decreasing amplitude of the microphone output signal, ~~wherein the signal process output signal is maintained during such times as the microphone output signal is disabled.~~

19. (Original) The method according to claim 18, wherein the incremental gain adjustment are in steps of between about 1 dB and about 10 dB.

20. (Original) The method according to claim 18, further comprising the steps of:
amplifying the signal process output signal using a first amplifier to produce a first amplified output signal; and
coupling the first amplified output signal to a first speaker input of a first speaker.

21. (Currently Amended) The method according to claims 20, further comprising the steps of:
filtering the signal process output signal using a low-pass filter to produce a filtered output signal;
amplifying the filtered output signal using a second amplifier to reproduce a second amplified output signal; and

CUSTOMER NO.: 24498**Serial No. 10/789,425**

Reply to Office Action dated: 7/30/07

Response dated: 11/20/07

**PATENT
PRN-012**

coupling the ~~first~~ second amplified output signal to a ~~second speaker an~~
input of a second speaker.

22. (Currently Amended) A method of enhanced intelligibility of a reproduced audio program signal in the presence of ambient noise in a speaker system comprising the steps of:

- receiving the reproduced audio program signal;
- monitoring ambient noise signals using a microphone to provide a microphone output signal;
- enabling the microphone output signal during first increments of time when the reproduced audio program signal is substantially off, and
- disabling the microphone output signal during second increments of time when the reproduced audio program signal is on, such that the microphone output signal includes ambient noise signal without including reproduced program signal components; and
- processing the reproduced audio program signal and the microphone output signal using a second transfer ~~signal~~ function, the second transfer function providing increasing high frequency response of the reproduced audio program signal as function of a decreasing amplitude of the microphone output signal, and vice versa, wherein the signal process output signal is maintained during such times as the microphone output signal is disabled.

23. (Original) The method according to claim 22, further comprising the steps of;

- amplifying the signal process output signal using a first amplifier to produce a first amplified output signal; and
- coupling the first amplified output signal to a first speaker input of a first speaker.

24. (Currently Amended) The method according to claim 23, further comprising the steps of:

- filtering the signal process output signal using a low-pass filter to produce a filtered output signal;

CUSTOMER NO.: 24498**Serial No. 10/789,425**

Reply to Office Action dated: 7/30/07

Response dated: 11/20/07

**PATENT
PRN-012**

amplifying the filtered output signal using a second amplifier to produce a second amplified output signal; and
coupling the first second amplified output signal to a ~~second speaker~~ an input of a second speaker.

25. (Currently Amended) A method of enhanced intelligibility of a reproduced audio program signal in the presence of ambient noise in a speaker system comprising the steps of:

receiving the reproduced audio program signal;
monitoring ambient noise signals using a microphone to provide a microphone output signal;
enabling the microphone output signal during first increments of time when the reproduced audio program signal is substantially off, and
disabling the microphone output signal during second increments of time when the reproduced audio program signal is on, such that the microphone output signal includes ambient noise signal components without including reproduced program signal components; and
processing the reproduced audio program signal and the microphone output signal using a first transfer function ~~signal~~ and a second transfer function ~~output signal~~, the first and second transfer functions having at least one signal process output signal, wherein:

the first transfer function provides incrementally increasing gain adjustments to the reproduced audio program signal as a function of an increasing amplitude of the microphone output signal and vice versa;
the second transfer function provides increasing high frequency response of the reproduced audio program signal, and vice versa; and
the least one signal process output signal is maintained during such times as the microphone output signal is disabled.

26. (Original) The method according to claim 25, wherein the incremental gain adjustments are in steps of between about 1 dB about 10 db.

CUSTOMER NO.: 24498**Serial No. 10/789,425**

Reply to Office Action dated: 7/30/07

Response dated: 11/20/07

**PATENT
PRN-012**

27. (Original) The method according to claim 25, further comprising the steps of:
 amplifying the at least one signal; and
 coupling the first amplified output signal to a first speaker input of a first
 speaker.

28. (Currently Amended) The method according to claim 27, further comprising the
steps of:

 filtering the at least one signal process output signal using a low-pass filter
 to produce a filtered output signal;
 amplifying the filtered output signal using a second amplifier to produce a
 second amplified output signal; and
 coupling the ~~first~~ second amplified output signal to a second speaker input
 of a second speaker.